

## Preliminary Product Datasheet

### High Performance Terminal Unit – Fusion 422

#### General Description

TTControl **Fusion** is a terminal unit with a high-performance multicore processor, able to drive multiple remote displays and offering rich 1000BASE-T1, 100BASE-T1 connectivity.

The separation of the computing unit from the display functions allows for freedom in the deployment of application windows and flexibility in the number of displays and their position in the operator cabin.

#### Specifications

Parameter		Unit
ECU Dimensions	244 x 198 x 45	mm
Dimensions for minimum connector release clearance	TBD	mm
Weight	TBD	g
Connector	2x HSD Display connectors 1x MOLEX 48-Pin Automotive Connector 4x H-MTD *BASE-T1 2x HSD USB	
Operating Temperature	-40 to 70	°C
Operating Altitude	0 to 4000	m
Supply Voltage	9 to 32	V
Peak Supply Voltage	40	V <sub>max</sub>
Supply Current at 12/24V without load	TBD	mA <sub>max</sub>
Standby Current	<1	mA <sub>max</sub>
Total Load Current	TBD	A <sub>max</sub>

#### Standards

CE-Mark	2014/30/EU 2006/42/EC
E-Mark	ECE-R10 Rev.4
EMC	EN 13309 ISO 14982 ISO 13766 EN 55035 EN 61131-2
ESD	ISO 10605
Electrical	ISO 16750-2 ISO 7637-2,-3
Ingress Protection	IP67 IP6K9K
Climatic	ISO 16750-4
Mechanical	ISO 16750-3

#### Features

- NXP i.MX8 application processor (QuadPlus)
- RAM 4GB
- FLASH 16GB
- RTC buffered by supercapacitor


#### Interfaces

- 3x CAN FD, 2x Standard CAN (1x ISOBUS compliant)
- 2x 100BASE-T1 + 2 x1000Base-T1
- 2x FPD Link III Display Interface
- 2x GMSL2
- A2B Master Interface
- 2x USB 2.0
- 1x RS232
- 1x LIN
- 1x K15 Input
- 1x Wake-up pin
- 6x GPIOs (2x HS DOUT and 4x DIN)

#### Software features

- Linux OS on Performance Host

## Block Diagram



## Housing and Connector

Aluminum baseplate with metal top

For further information, including price and availability, please contact [products@ttcontrol.com](mailto:products@ttcontrol.com)

Subject to changes and corrections. TTC 2300 is a product name of TTCControl GmbH. CODESYS is a trademark of 3S Smart Software Solutions GmbH. CANopen is a trademark of CAN in Automation (CiA). All other trademarks are the property of their respective holders. To the extent possible under applicable law TTCControl hereby disclaims any and all liability for the content and use of this product flyer.