

High-end Safety Controller – TTC 2740

General Description

TTC 2740 is a robust and powerful high-end electronic control solution for use in off-highway applications. The TTC 2740 is equipped with Infineon's TriCore™ Aurix™ TC399 CPU designed to fulfil the requirements in demanding safety-relevant construction, agricultural, municipal, material handling and automotive applications.

The TTC 2740 is part of a complete and compatible product family and is protected by a compact, automotive-style housing suited to mobile and stationary applications in harsh environments.

Specifications

Parameter		Unit
ECU Dimensions	220.5 x 315.0 x 41.2	mm
Dimensions for minimum connector release clearance	70 x 180 x 50 70 x 235 x 50	mm
Weight	2652	g
Connector	4 x 48-pin + 1 x 2-slot HSD	
Operating Temperature	-40 to +85	°C
Operating Altitude	0 to 4000	m
Supply Voltage	8 to 32	V
Maximum Supply Current at 12/24V without load	340/190	mA _{max}
Maximum Standby Current	<1	mA _{max}
Maximum Total Load Current	80	A

Standards

Functional safety	IEC 61508 SIL2 EN ISO 13849 PL d ISO 25119 AgPL d SRL2 ISO 26262 ASIL C ISO 19014 MPL d
CE-Mark	2014/30/EU 2006/42/EC
E-Mark	ECE-R10 Rev.6
FCC-Mark	47 CFR Part 15B, Class A
EMC	EN 13766 ISO 14982 CISPR 25 IEC 61000-4-2/-3/-4/-5/-6/-8
ESD	ISO 10605 IEC 61000 -6-4
Electrical	ISO 16750-2 ISO 7637-2, -3
Ingress Protection	EN 60529 IP65 and IP67 ISO 20653 IP6k9k
Climatic	ISO 16750-4
Mechanical	ISO 16750-3
ISOBUS	ISO 11783

Software

- C Programming Environment with real-time operating system



Features

CPU Core

- 32-Bit Infineon TriCore™ Aurix™ TC399
- 6 cores (4 lockstep cores) running at 300 MHz and memory protection for safety-relevant applications
- Floating-Point Unit and Hardware Security Module
- 6.47 MB int. SRAM, 16 MB int. Flash
- 32 MB ext. Flash, 1 MB internal EEPROM Emulation

Interfaces

- 8 x CAN FD 50 kbit/s up to 2 Mbit/s (1 x CAN FD with wake-up capability and 1 x CAN FD ISOBUS)
- 1 x CAN bus termination configurable via connector pins
- 2 x 100BASE-T1 (internal configurable Ethernet switch)
- 4 x SENT with SPC support*, 2 x LIN
- 1 x Real Time Clock (with external supply)

Outputs

- 46 x PWM OUT up to 1 kHz or digital OUT, up to 4 A (6 x up to 8 A), high side, with current measurement alternative use as digital timer IN (0.1 Hz - 20 kHz) configurable pull-up in groups of 2 or analog IN 12 bit, 0 - 32 V with configurable pull-up or LED control OUT*
- 12 x digital OUT up to 4 A, high side, current sense alternative use as PVG OUT, 10 - 90% of BAT+ or 4x as voltage OUT 0 - 10 V or LED control OUT* or analog IN 12 bit, 0-32V or (1x) Emergency stop OUT*
- 12 x digital OUT up to 4 A, low side, current sense or alternative use as analog IN 12 bit 0 - 5V/0 - 32V
- 3 x Status LED

Inputs

- 32 x analog IN 12 bit, 0-5V with configurable pull up/down, 0 - 25 mA, 0 - 100 kOhm, LED control
- 8 x digital timer IN (0.1 Hz - 20 kHz), encoder support, configurable pull-up/down, support for 7/14 mA current loop speed-sensor alternative use as analog IN 12 bit, 0 - 32 V, 0 - 25 mA
- 8 x digital timer IN (0.1 Hz - 20 kHz), encoder support, configurable pull-up alternative use as analog IN 12 bit, 0 - 32 V or (4x) SENT interfaces
- 14 x analog IN 12 bit, 0 - 5 V, 0 - 32 V with configurable pull up/down or (2x) Emergency stop IN*
- Terminal 15 and Wake-Up

Sensor supply

- 4 x sensor supply, 5 V, max. 500 mA
- 1 x sensor supply, 5 - 12 V, max. 2.5 W, configurable by SW in 0.5 V steps


All inputs and outputs supporting analog IN can also be used as digital Input.

All I/Os and interfaces are protected against short circuit to GND and BAT+ and can be configured by software.

Board temperature, sensor supply, and supply voltage are monitored by software. Three independent shut-off groups for PWM output stages. Details to the standards can be found in the System-Manual.

*upcoming feature

Block Diagram




Housing and Connector

Aluminum die-cast housing

Main connectors:

4 x 48-pin connectors

1 x 2-slot HSD connector



For further information, including price and availability, please contact products@ttcontrol.com

Subject to changes and corrections. TTC 2740 is a product name of TTControl GmbH. CODESYS is a trademark of 3S Smart Software Solutions GmbH. CANopen is a trademark of CAN in Automation (CiA). All other trademarks are the property of their respective holders. To the extent possible under applicable law TTControl hereby disclaims any and all liability for the content and use of this product flyer.