

# Vision 304t

## Description

Vision 304t is a compact 4.3-inch display available with touch screen. The display is optically bonded for perfect sunlight readability. The housing is sealed, and the device can withstand wide range of temperatures as well as shocks and vibrations.

#### Specifications

Display diagonal size	4.3", 15:9 aspect ratio
Dimensions	123 x 89 x 35 mm
Weight	560 g
Resolution	480 (W) x 272 (H) pixels
LCD type	TFT color graphic; optically bonded; projective- capacitive touch. Optional: without touch screen
Backlight	LED

#### **Optical Characteristics**

Luminance	800 cd /m² typ.
Viewing angle	V = +/- 70 deg. H = +/- 70 deg.
Contrast ratio	800:1

## **Maximum Ratings**

Operating temperature	-30 to +65 °C (ambient)
Storage temperature	-40 to +85 °C
Supply voltage	9 to 36 V

#### Standards

CE-Mark	2014/30/EU
E-Mark	ECE 10R
EMC	ISO 16750-2
	ISO 15003
Mechanical	ISO 16750-3
	ISO 15003
Ingress protection	ISO 20653 IP66



#### System components

- Freescale i.MX6 ULL application processor, 32bit ARM, 528 MHz
- 2 GB Flash, 256 MB RAM
- Runtime counter not buffered
- Stand-alone or in-dash mount, landscape or portrait orientation
- Projective capacitive touch screen
- · Optically bonded
- Optional: without the touchscreen and buzzer

#### Interfaces

- 2 x CAN, 10 kbit/s up to 1 Mbit/s
- 1 x USB 2.0 (Type C)
- Terminal 15 key switch (ignition)
- LED backlight
- Buzzer


# Software

• Programmable with CODESYS® V3 with enhanced target visualization, including support for CANopen® master or C/C++

Reverse polarity protection and protection of all external interfaces (except USB) against short circuit to GND and BAT+.



# **Block Diagram**



Copyright © TTControl GmbH. All rights reserved.

Subject to changes and corrections. Vision 304 is a product name of TTControl GmbH. CODESYS® is a registered trademark of CODESYS GmbH. CANopen® and CiA® are registered community trademarks of CAN in Automation). All other trademarks are the property of their respective holders. To the extent possible under applicable law, TTControl hereby disclaims any and all liability for the content and use of this product flyer.